

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-264 (B)

Product code : 000000121422

Type of product : liquid

#### Recommended use of the chemical and restrictions on use

Product use : Epoxy coating, Product is not intended for consumer use

#### Manufacturer or supplier's details

Company : Sika (NZ) Ltd.  
85-91 Patiki Road  
Avondale  
Auckland AKL 1026

Telephone : +64 9 820 2900

Emergency telephone number : 0800 734 607

Telefax : +64 9 828 4091

E-mail address : info@nz.sika.com

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable Liquids : Category D

Acute toxicity (Oral) : Category D

Acute toxicity (Dermal) : Category D

Skin corrosion : Category C

Serious eye damage : Category A

Skin sensitisation : Category B

Toxic to Reproduction : Category B

Aquatic toxicity (Acute or Chronic) : Category B

Ecotoxic to soil environment : Category B

Ecotoxic to terrestrial vertebrates : Category C

#### GHS label elements

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H227 Combustible liquid.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H361 Suspected of damaging fertility or the unborn child.  
H411 Toxic to aquatic life with long lasting effects.  
H422 Toxic to the soil environment.  
H433 Harmful to terrestrial vertebrates.

Precautionary statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P322 Specific measures (see supplemental first aid instructions on this label).  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.  
P391 Collect spillage.  
**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
**Disposal:**

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Polyaminoamide

#### Hazardous components

Chemical name	CAS-No.	Concentration (%)
benzyl alcohol	100-51-6	>= 30 - < 50
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 10 - < 20
m-phenylenebis(methylamine)	1477-55-0	>= 10 - < 20
Hydrocarbons, C9, aromatics	64742-95-6	>= 1 - < 10
Phenol, dodecyl-, branched	121158-58-5	>= 1 - < 10
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 1 - < 10

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.  
corrosive effects  
sensitising effects  
Gastrointestinal discomfort

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Harmful if swallowed or in contact with skin  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Suspected of damaging fertility or the unborn child.  
Causes severe burns.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : Water
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours or spray mist.

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Avoid exceeding the given occupational exposure limits (see section 8).

Do not get in eyes, on skin, or on clothing.

For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the application area.

Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
m-phenylenebis(methylamine)	1477-55-0	WES-Ceiling	0.1 mg/m3	NZ OEL
		Further information: Skin absorption		
		C	0.1 mg/m3	ACGIH
Hydrocarbons, C9, aromatics	64742-95-6	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : yellow
- Odour : amine-like
- Odour Threshold : No data available
- pH : ca. 11
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : ca. 68 °C (154 °F)  
Method: closed cup
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 4.9996 hPa (3.750 mmHg)
- Relative vapour density : No data available
- Density : ca. 1 g/cm<sup>3</sup> (20 °C (68 °F) ())
- Solubility(ies)  
Water solubility : insoluble
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : ca.  
420 °C (788 °F)
- Decomposition temperature : No data available
- Viscosity  
Viscosity, dynamic : No data available

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)  
Explosive properties : No data available  
Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : The product is chemically stable.  
Possibility of hazardous reactions : Stable under recommended storage conditions.  
Conditions to avoid : No data available  
Incompatible materials : No data available  
No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if swallowed or in contact with skin

#### Components:

##### **benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

##### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### **Phenol, dodecyl-, branched:**

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Acute oral toxicity : LD50 Oral (Rat): 2,140 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,000 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

### **Components:**

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Assessment: The product is a skin sensitiser, sub-category 1A.

Result: The product is a skin sensitiser, sub-category 1A.

### **Chronic toxicity**

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Components:**

##### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100  
mg/l  
Exposure time: 72 h

##### **m-phenylenebis(methylamine):**



# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
aquatic invertebrates Exposure time: 48 h

### Hydrocarbons, C9, aromatics:

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9  
mg/l  
Exposure time: 72 h

### Phenol, dodecyl-, branched:

Toxicity to fish : LC50 (Fish): 0.14 mg/l  
Exposure time: 96 h  
Method: see user defined free text

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 0.01 - 0.1 mg/l  
aquatic invertebrates Exposure time: 48 h  
Method: OECD Test Guideline 202

M-Factor (Acute aquatic tox- : 10  
icity)

M-Factor (Chronic aquatic : 10  
toxicity)

### 2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10  
- 100 mg/l  
Exposure time: 72 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

### Product:

Additional ecological infor- : An environmental hazard cannot be excluded in the event of  
mation unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemi-  
cal or used container.  
Send to a licensed waste management company.

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1760  
Proper shipping name : Corrosive liquid, n.o.s.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, solvent naphtha)  
Class : 8  
Packing group : III  
Labels : 8  
Packing instruction (cargo aircraft) : 856  
Packing instruction (passenger aircraft) : 852

##### IMDG-Code

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, solvent naphtha)  
Class : 8  
Packing group : III  
Labels : 8  
EmS Code : F-A, S-B  
Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### NZS 5433

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, solvent naphtha)  
Class : 8  
Packing group : III  
Labels : 8

---

### SECTION 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

# SAFETY DATA SHEET

## Sikafloor®-264 (B)



Version 0.0

SDS Number: 000000121422

Revision Date: 2016/09/16

---

### HSNO Approval Number

HSR002659

### HSNO Controls

Approved handler certificate not required.

HSNO tracking not required.

Refer to EPA user guide to the HSNO control regulations for further information.

### The components of this product are reported in the following inventories:

NZIoC : On the inventory, or in compliance with the inventory

---

## SECTION 16. OTHER INFORMATION

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.