

Pulastic Deep Clean

Intensive Cleaning Detergent

General	<ul style="list-style-type: none"> ■ Aggressive cleaning detergent supplied by a company certified according ISO 9001:2000 for quality control and ISO 14001 for environmental care. ■ Final quality starts with preparation. A good renovation job starts with a thorough cleaning of the existing floor, so that's why Descol offers PULASTIC DEEP CLEAN - the best way to degrease your Pulastic surface before a renovation. ■ PULASTIC DEEP CLEAN is a intensive cleaning detergent for the second stage (as from approximately 6 months after delivery of the Pulastic floor) of the cleaning process, for Pulastic indoor sports floors finished with both a water based and solvent based Pulastic sports floor coating. ■ PULASTIC DEEP CLEAN is a low sudsing/bubbling detergent specially developed to thoroughly remove grease, wax and dirt from the floor. PULASTIC DEEP CLEAN is excellent for use in scrub-suck machines. ■ PULASTIC DEEP CLEAN is a detergent made of a concentrated blend of amines and non ionogenic surfactants. The product offers highly effective cleaning properties. With a pleasant, fresh fragrance PULASTIC DEEP CLEAN is a friendly product to the user. ■ PULASTIC DEEP CLEAN is not a regular maintenance cleaning detergent!
User Instructions	<ul style="list-style-type: none"> ■ Always add PULASTIC DEEP CLEAN to water, not the other way around. The use of lukewarm water (max 40 °C) increases the functioning. ■ For intensive cleaning with PULASTIC DEEP CLEAN: 1 part Pulastic Deep Clean to 10 parts water, using a medium-type scrubbing pad (e.g. Scotch Brite – Green) and allow the agent to do its work, but prevent it from drying up!
Technical Data	
Packaging	5 Litre bottle
Storage	between 0 - 40 °C. Protect against frost.
Consistency	liquid
Colour	Neutral
Density	1.090 gram/liter
pH-value	11.5 - 12
Legal Notes	<p>The information, and, in particular, the recommendations relating to the application and end-use of Descol products, are given in good faith based on Descol's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.</p>

